



SPAWER

O'SPA Flow

3kW | 5kW | 7kW

The SPA heat pump with integrated circulation

Thanks to its integrated circulation pump, the O'SPA Flow connects directly to the SPA, without a bypass. It manages both heating and cooling temperatures, down to ice bath mode, for easy use and precise control all year round.

- ➡ **Integrated circulation pump :** Constant flow rate adapted to SPAs, without bypass, ensuring stable flow through the heat exchanger for simplified installation and optimized thermal regulation.
- ➡ **SPA heater control via integrated relay :** The O'SPA Flow can control the spa's electric heater via an integrated relay, ensuring heating continuity when required.
- ➡ **Complete thermal management :** High-efficiency heating and integrated chiller.

- ➡ **Compact & premium design :** With its compact format, clean aesthetics and decorative grilles, the O'SPA Flow is designed to blend naturally next to the SPA.
- ➡ **The heat pump covers all SPA thermal needs :** Fast temperature rise, precise temperature maintenance, cooling during hot periods or for cold baths, and automatic mode for hands-free operation.



Compatible with all water treatments



Built-in WiFi

WARRANTIES

| | |
|--------------------------------|-----------------|
| Heat pump | 2 YEARS |
| Compressor | 5 YEARS |
| Titanium coil (anti-corrosion) | 10 YEARS |

INTEGRATED
circulation pump

OPERATES
down to -7°C

3 versions
AVAILABLE

POOLEX
FOLLOW THE EXPERT

| O'SPA FLOW | | 3 kW | 5 kW | 7 kW |
|-----------------------------------|---|---------------|---------------|------|
| Reference : PC-OSPA | | 34 | 54 | 74 |
| Recommended climate (heating) | | Warm | Temperate | |
| Air 26°C | Capacity (kW) | 3,30 | 5,06 | 7,10 |
| Water 26°C | Power consumption (kW) | 0,66 | 0,95 | 1,28 |
| Humidity 80% | COP | 5 | 5,30 | 5,55 |
| Air 15°C | Capacity (kW) | 2,11 | 3,25 | 4,65 |
| Water 38°C | Power consumption (kW) | 0,75 | 1,08 | 1,37 |
| Humidity 70% | COP | 2,75 | 3,00 | 3,40 |
| Recommended climate (cooling) | | Temperate | | Warm |
| Air 35°C | Capacity (kW) | 2,00 | 2,75 | 3,90 |
| Water 27°C | Power consumption (kW) | 0,98 | 1,38 | 1,66 |
| Humidity 70% | EER | 2,05 | 2,00 | 2,35 |
| Air 15°C | Capacity (kW) | 1,45 | 2,00 | 2,90 |
| Water 5°C | Power consumption (kW) | 0,62 | 0,76 | 1,00 |
| Humidity 70% | EER | 2,35 | 2,55 | 2,90 |
| Power supply | Single-phase 220-240V ~ 50Hz | | | |
| Connections | 32 / 38mm | | | |
| Max power (kW) | 1,30 | 1,80 | 2,55 | |
| Heating temperature range | 10°C / 40°C | | | |
| Cooling range | 2°C / 30°C | | | |
| Operating range (heating/cooling) | -10°C~43°C / 7°C~40°C | | | |
| Flow rate (m³/h) | 1,40 | 2,15 | 3,00 | |
| Refrigerant | R32 / 0,24 kg | R32 / 0,40 kg | R32 / 0,45 kg | |
| Packaging dimensions (mm) | 585x560x430 | | 685x590x483 | |
| Dimensions (mm) | 580x490x390 | | 620x490x430 | |
| Net / gross weight (kg) | 33 / 38 | 38 / 43 | 47 / 50 | |
| Noise at 1 m (dB(A)) | < 50 | < 50 | < 55 | |
| Noise at 10 m (dB(A)) | < 30 | < 30 | < 35 | |
| Compressor type | Rotary | | | |
| Heat exchanger | Twisted Tech© Titane | | | |
| Function | Heating + Chiller + Auto + SPA heater relay control | | | |
| Pressure drop (mCW) | 2,5 | 2,5 | 3,0 | |

Specially developed for spas, Nordic baths and small pools, the O'SPA Flow combines heating, cooling and water circulation in a compact unit.

Its integrated circulation pump eliminates the need for a bypass and ensures a stable flow rate, perfectly suited to spas (simple connection).

Thanks to its chiller function, it can lower the water temperature down to 2°C, ideal for cold baths, recovery or hot climates. Available in 3 kW, 5 kW and 7 kW, it adapts to all configurations and ensures optimal operation thanks to its ON/OFF mode calibrated according to ambient temperature.

The O'SPA Flow offers simple and intuitive connected control, allowing remote adjustment of temperature and operating modes via the Poolex mobile app.

COMPACT DIMENSIONS :



Accessories

INCLUDED



Control relay



Residual current device with 5 m cable



Hydraulic connectors (2 sets)



Hose clamps (2 sets)



NetSpa kit connectors

OPTIONAL



Remote touchscreen



Hydraulic connection kit